


Summit 1800i

Semi-Automated, High Precision Rework System



**Largest Installed Base • Excellent Thermal Performance • Process Flexibility
Ease of Operation • Global Support • Industry Leading Reliability**

Auto Profiling Capability – Fast and easy profile creation. Simply enter the desired product temperatures. After thermal profile is created, the entire reflow process is built automatically and ready to run.

“1-2-3-Go” Graphical User Interface – Proprietary SierraMate™ Windows® based software provides an easy to use “1-2-3-Go” graphical user interface increasing user friendliness.

Nitrogen Inert Environment – Programmable process control applies nitrogen only when needed.

- Maximized N2 savings

Comprehensive Tooling – Wide range of tooling available to meet your current and future rework needs.

Efficient Convection Heating – Closed-loop temperature control ensures a more even heat distribution as compared to IR heating.

- Boost flow increases heating capacity at lower temperatures
- Industry-leading speed, control, repeatability

Independent Pick and Place – Motorized reflow head driven by an advanced motion system with programmable force control provides precision with total flexibility.


Non-Contact Site Scavenging – Dynamic height sensing control of distance between the scavenger tip and PCB (scavenger gap).

Industry 4.0 Compliant – Automated data/event logging directly to your EMS.


- Enhanced profile sharing and user collaboration




SOLDER SCAVENGER WITH DYNAMIC HEIGHT SENSING




1-2-3-GO SIERRAMATE™ GRAPHICAL USER INTERFACE




UP TO 80MM SQUARE FOV



DUAL CONVECTION BOTTOM HEATERS



01005 REWORK



OPTICAL ALIGNMENT SYSTEM

Technical Specifications

Placement Capability	0.0005" (12μ) mean + 3σ	
Top Heater	1.6kW Focused Convection 2.2kW Boost Heat Mode	
Bottom Heater	4.0kW Convection Plenum	7.8kW NextGen Plenum (option)
Z-Axis Motion	Independent & Programmable Z-Height Pickup Tube Independent & Programmable Z-Height Top Heater	
Theta Motion	Programmable Motorized Theta - 360°	
Field of View	2.5" (65mm) Square	3.2" (80mm) Square (option)
Max Board Size	18x22" (455x560mm)	22x30" (560x760mm) (option)
Component Range	0.005" (0.12mm) to 8" (200mm) Connectors	
Temperature Control	K-Type Thermocouple (Closed-Loop)	
Thermocouple Jacks	6	14 (option)
Compliance	CE, CAN/CSA, UL 61010-1	
Special Features	Automatic Component and Vision Shuttle Programmable Placement Force Control Automatic Component Height Sensing & Alignment Height	

Why choose VJ Electronix

In a highly competitive SMT manufacturing market, quality and productivity are critical. VJ Electronix develops and manufactures all their products with this in mind. For decades, we have secured leading positions in a variety of markets through technological firsts and a variety of innovative customer-specific solutions.

VJ Electronix is the leader in PCB rework, x-ray inspection and x-ray counting systems. VJ Electronix's equipment help improve manufacturing costs and product quality.

VJ Electronix
19 Alpha Road
Chelmsford, MA, 01824
USA

Phone: +1 978 486 4777
www.vjelectronix.com

VJ Offices:
Bohemia NY
East Haven CT
Monterey, Mexico

Hartzviller, France
Bengaluru, India
Budapest, Hungary